

<b>Appliance Hardware Comparison Chart</b>					
<b>Model #</b>	<b>NS-3000</b>	<b>HS-4000</b>	<b>NS-6000</b>	<b>HS-7000<sup>1</sup></b>	<b>HS-9000</b>
Mfg Model #	<a href="#">NEI S1200</a>	<a href="#">HP DL160</a>	<a href="#">NEI S1400</a>	<a href="#">HP DL360</a>	<a href="#">HP DL380</a>
Form Factor	Mini 1U Rackmount	1U Rackmount	1U Rackmount	1U Rackmount	2U Rackmount
Dimensions	16.8" x 1.7" x 14.0"	17.64 x 1.70 x 26.85in (44.80 x 4.32 x 68.20cm) 32 lb (14.55 kg)	16.78" x 1.7" x 22.6"	16.78 x 1.70 x 27.25in (42.62 x 4.32 x 69.22cm)34 lb (14.45 kg)	17.54 x 3.38 x 26.01 in (44.54 x 8.59 x 66.07 cm)50 lb (22.72 kg)
Processor	Intel® Core Duo 2.13GHz	Intel® Quad Core Xeon® 2.00GHz	Intel® Quad Core Xeon® 2.66 GHz	Intel® Quad Core Xeon® 2.50GHz	2 x Intel® Quad Core Xeon® 3.00GHz
Memory	4GB 667MHz DDR2 RAM	4 GB Fully Buffered DIMM DDR-2-667	4 GB 667MHz DDR2 RAM	4 GB Fully Buffered DIMM DDR-2-667	4Gb Fully Buffered DIMM DDR-2-667
Front bus speed / Cache s	1066 MHz/2 Mb	1333 MHz/12 Mb	1333 MHz/6 Mb	1333 MHz/12 Mb	1333 MHz/12 Mb
Hard drive	1 250 GB SATA	2 x 160 GB SATA Non- hot plug RAID1	2 x 250 GB SATA hot- swap RAID1	2 x 146 GB hot-plug 2.5 SAS RAID1 10,000rpm <sup>1</sup>	4 x 146 GB hot-plug 2.5 SAS RAID10
Network Interface	4 x Gigabit Ethernet ports	4 x Gigabit Ethernet ports	4 x Gigabit Ethernet ports	4 x Gigabit Ethernet ports <sup>1</sup>	4 x Gigabit Ethernet ports
Support Options	1, 2 and 3-year support packages	1 - 5 year support packages up to 4-hour onsite	1, 2 and 3-year support packages	1 - 5 year support packages up to 4-hour onsite	1 - 5 year support packages up to 4-hour onsite
Remote Management	PSAM	HP Lights Out 100i, PSAM	PSAM	HP Lights Out 2, PSAM	HP Lights Out 2, PSAM

<sup>1</sup>HS-WEB7000L contains 4 x 146 GB hot-plug 2.5 SAS RAID1 10,000rpm and 2 Ethernet ports